## **MULE PRO-FX™ EPS LE**







## **POWER**

**Engine** 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

**Maximum Torque** 48.0 lb-ft @ 3,500 rpm

**Bore x Stroke** 2.83x2.62 in

**Compression Ratio** 9.5:1

DFI® with 34mm throttle body **Fuel System** 

Continuously Variable Transmission (CVT) with (H,L,N,R) **Transmission** 

**Final Drive** Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

**Engine Braking** Yes

**Alternator Output** 

(max)

CAPABILITY

Front Suspension /

**Wheel Travel** 

75 amp

Double wishbone/8.7 in

Rear Suspension /

Wheel Travel

Double wishbone/8.5 in (L) /8.7 in (R)

**Front Tires** 26x9.00-12, radial

**Rear Tires** 26x11.00-12, radial

Steering Electric Power Steering (EPS), Tilt steering

**Park Brake Type** Independent, Mechanical Disc

**Front Brakes** Dual Disc, 2 piston caliper

Rear Brakes Dual Disc, 1 piston caliper **Ground Clearance** 10.4 in

**Fuel Capacity** 7.9 gal

**Cargo Bed** 54.1 x 53.3 x 11.0 in

**Cargo Bed Load** 999 lb / 600.0 lb CA Model

16.0 ft

Capacity

**Dimensions (LxWxH)** 

**Turning Radius** 

**Payload Capacity** 1,616.3 lb / 1,263.5 for CA Model

**Seating Capacity** 

**Towing Capacity** 2.000 lb

Lighting (2) Halogen headlights. (2) LED headlights

## **DETAILS**

**Overall Length** 133.3 in

**Overall Width** 64.0 in

**Overall Height** 79.7 in

**Curb Weight** 1,832.4 lb\*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters,

2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse

and parking indicators, seatbelt reminder lamps

**Wheel Type** Alloy

**Additional Features** Roof, Cast Aluminum Wheels

**Color Choices** Firecracker Red

Kawasaki STRONG 3-Year Limited Warranty Warranty



