VULCAN® 1700 VOYAGER® ABS









D	n	V	M	С	D
Г	u	ľ	V	C	П

Engine 4-stroke, 52-degree V-twin, liquid-cooled

1,700cc/103.7 cu in **Displacement**

Bore x Stroke 102.0 x 104.0mm

Compression Ratio

Maximum 107.6 lb-ft @ 2,750 rpm

9.5:1

Torque Fuel System

DFI® with 42mm throttle bodies (2)

TCBI with Electronic Advance Ignition

Transmission 6-speed with overdrive and positive neutral

finder

Final Drive Carbon fiber-reinforced belt

Electronic Rider Electronic Cruise Control, Kawasaki Advanced Coactive-Braking Technology (K-ACT) ABS

Aids

PERFORMANCE

Front Suspension / **Wheel Travel** 45mm Showa telescopic fork/5.5 in

Rear Suspension / Wheel Travel

Swingarm with twin air-assisted shocks, with 4-way rebound damping/3.1 in

Front Tire 130/90-16 **Rear Tire** 170/70-16

Front Brakes Dual 300mm discs, dual four-piston calipers,

K-ACT ABS

Rear Brakes Single 300mm disc, twin-piston caliper, K-ACT

DETAILS

Steel, double-cradle with box-section single-**Frame Type** tube backbone

Rake/Trail 30° /7.0 in

Overall Length 100.8 in

Overall Width 39.2 in

Overall Height 61.0 in

Ground 5.3 in Clearance

Seat Height 28.7 in

Curb Weight 895.2 lb*

Fuel Capacity 5.3 gal

Wheelbase 65.6 in

Special Features Integrated audio system with SiriusXM and

intercom headset compatibility

Color Choices Metallic Graphite Gray/Metallic Carbon Gray

36 Month Limited Warranty Warranty

Scan with camera to view videos. key features and more.

