²⁰²⁴ **KX™85**







POWER

Engine	2-stroke single with exhaust power valve (KIPS), liquid-cooled	
Displacement	84cc	
Bore x Stroke	48.5 x 45.8mm	
Compression Ratio	10.9:1 (low speed) / 9.0:1 (high speed)	
Fuel System	28mm Keihin carburetor	
Ignition	CDI with Digital Advance	
Transmission	6-speed, return shift, with wet multi-disc manual clutch	
Final Drive	Chain	

Rear Tire90/100-14Front BrakesSingle 220mm petal disc with dual-piston
caliperRear BrakesSingle 184mm petal disc with single-piston
caliper

DETAILS

d)			
-,	Frame Type	High-tensile steel perimeter design with subframe member	
	Rake/Trail	29°/3.8 in	
i-disc	Overall Length	72.0 in	
	Overall Width	30.1 in	
	Overall Height	43.3 in	
	Ground Clearance	11.4 in	
fork 10.8 in	Seat Height	32.7 in	
	Curb Weight	164.4 lb*	
24-way	Fuel Capacity	1.32 gal	
	Wheelbase	49.8 in	
	Color Choices	Lime Green	
	Warranty	Not Available	

PERFORMANCE

Front Suspension / Wheel Travel	36mm inverted telescopic cartridge fork with 20-way compression damping/10.8 in
Rear Suspension / Wheel Travel	Uni-Trak [®] single shock system with 24-way compression and 21-way rebound damping, plus adjustable spring preload/10.8 in
Front Tire	70/100-17





*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki-la.com for full product details.