MULE™ 4010 4x4









POWER

Engine 4-stroke, 2-cylinder, OHV, 90° V-twin, Liquid-cooled

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2,500 rpm

Bore x Stroke 2.99 x 2.68 in

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with

(H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear

differential with differential lock

Engine Braking

Alternator Output 23 amp

(max)

Rear Brakes Drum **Ground Clearance** 6.9 in

Fuel Capacity 6.3 gal

Turning Radius 11.2 ft

Cargo Bed Dimensions 46.3 x 51.6 x 11.4 in

(LxWxH)

Cargo Bed Load

Capacity

Payload Capacity 1,327 lb

800 lb

62.0 in

Seating Capacity

Towing Capacity 1,200 lb

Lighting (2) Halogen headlights (2) tail/brake lights

CAPABILITY

Front Suspension / MacPherson Strut/3.9 in **Wheel Travel**

Rear Suspension / Wheel Travel

DeDion Axle/2.8 in

Front Tires 23x11.00-10 **Rear Tires** 23x11.00-10

Steering Rack-and-pinion w/ Electric Power Steering (EPS)

Park Brake Type Independent, Mechanical Drum

Front Brakes Drum **Overall Length** 116.7 in **Overall Width**

DETAILS

Overall Height 75.8 in

Curb Weight 1,433.3 lb*

Wheelbase 73.6 in

Instruments Parking brake warning light, coolant temperature warning light, 12V DC outlet, fuel gauge, hour meter

Wheel Type Steel

Color Choices Dark Royal Red, Timberline Green

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

