MULE™ 4010 TRANS4x4®









Drum

7.1 in

6.3 gal

POWER

Engine 4-stroke, 2-cylinder, OHV, 90° V-twin, Liquid-cooled

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2,500 rpm

Bore x Stroke 2.99 x 2.68 in

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with

(H,L,N,R)

Final Drive

differential with differential lock

Engine Braking

Alternator Output 23 amp

(max)

Selectable 2WD/4WD, shaft. Dual mode rear

CAPABILITY

Front Suspension / MacPherson Strut/3.9 in **Wheel Travel**

Rear Suspension / Wheel Travel

DeDion Axle/2.8 in

Front Tires 23x11.00-10 23x11.00-10 **Rear Tires**

Steering Rack-and-pinion w/ Electric Power Steering (EPS)

Park Brake Type Independent, Mechanical Drum

Front Brakes Drum **Turning Radius** 12.8 ft **Cargo Bed Dimensions** (LxWxH) **Cargo Bed Load** 800 lb (2-person) / 401 lb (4-person)

Rear Brakes

Fuel Capacity

Ground Clearance

50.4 x 47.6 x 11.2 in (2-person) / 30.3 x 47.6 x 11.2 in (4-

Capacity

Payload Capacity 1,330 lb **Seating Capacity** 2-4

Towing Capacity 1,200 lb

Lighting (2) Halogen headlights (2) tail/brake lights

DETAILS

Overall Length 128.5 in **Overall Width** 58.5 in

Overall Height 75.8 in

Curb Weight 1,587.6 lb*

Wheelbase 85.2 in

Instruments Parking brake warning light, coolant temperature warning light, 12V DC outlet, fuel gauge, hour meter

Wheel Type Steel

Color Choices Dark Royal Red, Timberline Green

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

