

ALL-NEW 2024

RIDGE® RANCH EDITION



POWER		DETAILS	
Engine	4-stroke, DOHC, 4-valve In-Line Four-Cylinder, liquid-cooled	Frame	Ladder type, tubular steel
Displacement	999cc	Overall Length	126.4 in
Maximum Horsepower	92.0 hp ¹ @ 8,500 rpm	Overall Width	64.0 in
Maximum Torque	65.8 lb-ft @ 5,500 rpm	Overall Height	81.9 in
Bore x Stroke	73.4 x 59.0mm	Curb Weight	1,909.5/1,911.7 lb* CA Model
Compression Ratio	10.6:1	Wheelbase	90.7 in
Fuel System	EFI	Instruments	Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Bluetooth indicator, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil pressure, water temperature)
Ignition	TCBI with Digital Advance	Additional Features	WARN® VRX 45 Powersport Winch, Adjustable driver's seat, ERGO-FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDEOLGY THE APP Powersports, USB ports, KQR™ system compatible
Starting System	Electric	Color Choices	Metallic Stardust White
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)	Warranty	Kawasaki STRONG 3-Year Limited Warranty
Final Drive	Selectable 4WD with locking rear differential, shaft		
Engine Braking	Yes		
Alternator Output (max)	85 amp		
Electronic Rider Aids	Power Modes, Economical Riding Indicator		
CAPABILITY			
Front Suspension / Wheel Travel	Long-Travel, Double Wishbone/12.7 in		
Rear Suspension / Wheel Travel	Long-Travel, Double Wishbone/12.7 in		
Front Tires	Duro 27 x 9-14		
Rear Tires	Duro 27 x 11-14		
Wheel Type	14" Aluminum		
Steering	Rack-and-pinion w/ Electric Power Steering (EPS)		
Front Brakes	Dual hydraulic 249mm discs with two-piston calipers		
Rear Brakes	Dual hydraulic 249mm discs with single-piston calipers		

Scan with camera to view videos, key features and more.



^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
Specifications subject to change. Visit [Kawasaki-usa.com](https://www.kawasaki-usa.com) for full product details.