

2024

TERYX KRX® 4 1000 eS

Kawasaki

Let the Good Times Roll®



CANDY LIME GREEN/SUPER BLACK



POWER		Fuel Capacity	
Engine	4-stroke, DOHC, 8-valve parallel-twin, liquid cooled	Turning Radius	23.3 ft
Displacement	999cc	Cargo Bed Dimensions (LxWxH)	14.6 x 33.1 x 9.1 in
Maximum Torque	76.7 lb-ft @ 7,000 rpm	Cargo Bed Load Capacity	351 lb
Bore x Stroke	92.0 x 75.1mm	Payload Capacity	1,001 lb
Compression Ratio	11.5:1	Seating Capacity	4
Fuel System	DFI® with two 50mm throttle bodies	Towing Capacity	N/A
Ignition	TCBI with Electronic Advance	Lighting	(2) LED headlights, (2) LED taillights, LED stoplight
Starting System	Electric	DETAILS	
Transmission	Automatic CVT with centrifugal clutch (H,L,N,R)		
Final Drive	Selectable 2WD/4WD with locking front differential, shaft	Frame	Ladder type, tubular steel
Engine Braking	Yes	Overall Length	157.3 in
CAPABILITY		Overall Width	68.1 in
Front Suspension / Wheel Travel	Double wishbone, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/18.6 in	Overall Height	76.2 in
Rear Suspension / Wheel Travel	4-link trailing-arm rear suspension, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/21.1 in	Curb Weight	2,105.8 lb* / 2,108.0 lb* CA Model
Front Tires	Maxxis® Carnivore 31 x 10.00R15 8PR	Wheelbase	125.8 in
Rear Tires	Maxxis® Carnivore 31 x 10.00R15 8PR	Instruments	Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp.
Steering	Electric Power Steering (EPS) / rack-and-pinion	Wheel Type	Alloy wheels
Front Brakes	Dual hydraulic discs with two-piston calipers	Color Choices	Candy Lime Green/Super Black
Rear Brakes	Dual hydraulic discs with single-piston calipers	Warranty	6 Month Limited Warranty
Ground Clearance	15.2 in (max), 14.2 in (std)		

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [Kawasaki-la.com](https://www.kawasaki-la.com) for full product details.