## **Z H2 SE ABS**









## **POWER**

Engine 4-stroke, 4-cylinder, DOHC, 16-valve, liquid-cooled,

supercharged

Displacement 998cc

Bore x Stroke 76.0 x 55.0mm

Compression Ratio 11.2:1

Maximum Torque 101.0 lb-ft

Fuel System DFI® with 40mm throttle bodies

Ignition TCBI with Digital Advance

Transmission 6-speed dog-ring, return shift

Final Drive Sealed chain

**Electronic Rider** 

Aids

Kawasaki Electronic Control Suspension (KECS) with Showa Skyhook Technology, KECS Linked Integrated Riding Modes, Kawasaki Cornering Management Function (KCMF), Power Modes (3), Kawasaki Launch Control Mode (KLCM), Kawasaki TRaction Control (KTRC), Kawasaki Launch Control Mode (KLCM), Kawasaki Engine Brake Control (KEBC), Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Quick Shifter (KQS) (upshift & downshift), Electronic Cruise Control

## PERFORMANCE

Front Suspension / Wheel Travel

Showa SFF-BP Fork with KECS Compression and KECS Rebound Damping, plus Manual Spring Preload Adjustability/4.7 in Rear Suspension / Wheel Travel

Uni-Trak®, Showa Gas-Charged Shock with KECS Compression and KECS Damping, plus Manual Spring

Preload Adjustability/5.3 in

**Front Tire** 120/70-17

**Rear Tire** 190/55-17

Front Brakes Dual 320mm Disc with Radial-mount Brembo M4.32

Calipers, Kawasaki Intelligent anti-lock Brake System

(KIBS)

Rear Brakes Single 260mm disc with single-piston caliper,

Kawasaki Intelligent anti-lock Brake System (KIBS)

## **DETAILS**

Frame Type Trellis, high tensile steel

Rake/Trail 24.9°/4.1in

Overall Length 82.1 in

Overall Width 31.9 in

Overall Height 44.5 in

**Ground Clearance** 5.5 in

Seat Height 32.7 in

Curb Weight 531.4 lb\*

Fuel Capacity 5.0 gal

Wheelbase 57.3 in

Special Features Smartphone Connectivity via RIDEOLOGY THE APP, TFT

Instrumentation

Color Choices Metallic Matte Graphenesteel Gray/Ebony/Mirror

Coated Black

**Warranty** 12 Month Limited Warranty



