

2020
KX™ 250



POWER		Rear Tire	100/90-19
Engine	4-stroke single, DOHC, liquid-cooled	Front Brakes	Single semi-floating 270mm Braking® petal disc with dual-piston caliper
Displacement	249cc	Rear Brakes	Single 250mm Braking® petal disc with single-piston caliper
Bore x Stroke	78.0 x 52.2mm	DETAILS	
Compression Ratio	14.2:1	Frame Type	Aluminum perimeter
Fuel System	DFI® with 44mm Keihin throttle body and dual injectors	Rake/Trail	28.6° / 5.1 in
Ignition	Digital CDI	Overall Length	85.5 in
Transmission	5-speed, return shift, with wet multi-disc manual clutch	Overall Width	32.3 in
Final Drive	Chain	Overall Height	50.0 in
PERFORMANCE		Ground Clearance	13.1 in
Front Suspension / Wheel Travel	48mm inverted telescopic coil spring fork with 23-way compression damping and 20-way rebound damping/12.4 in	Seat Height	37.3 in
Rear Suspension / Wheel Travel	Uni-Trak® gas charged shock with piggyback reservoir with dual range (2 1/16 turns stepless high speed / 21-way low speed) and 38-way rebound damping and adjustable spring preload/12.2 in	Curb Weight	221.1 lb without fuel / 231.4 lb*
Front Tire	80/100-21	Fuel Capacity	1.69 gal
		Wheelbase	58.3 in
		Color Choices	Lime Green
		Warranty	Not Available

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [Kawasaki-la.com](https://www.kawasaki-usa.com) for full product details.