

2023

KLX®230R S



 LIME GREEN



POWER

Engine	4-stroke single, SOHC, air-cooled
Displacement	233cc
Bore x Stroke	67.0 x 66.0mm
Compression Ratio	9.4:1
Fuel System	DFI® with 32mm Keihin throttle body
Ignition	TCBI Electronic Advance
Transmission	6-speed, return shift with wet multi-disc manual clutch
Final Drive	Chain

Rear Tire	100/100-18
Front Brakes	Single 240mm petal disc with a dual-piston caliper
Rear Brakes	Single 220mm petal disc with single-piston caliper

DETAILS

Frame Type	High-tensile steel, box-section perimeter
Rake/Trail	25.7° /4.3 in
Overall Length	80.1 in
Overall Width	33.1 in
Overall Height	46.3 in
Ground Clearance	10.8 in
Seat Height	35.4 in
Curb Weight	262.3 lb.*
Fuel Capacity	1.7 gal
Wheelbase	53.1 in
Color Choices	Lime Green
Warranty	6 Months

PERFORMANCE

Front Suspension / Wheel Travel	37mm telescopic fork/8.7 in
Rear Suspension / Wheel Travel	Uni-Trak® linkage system and single shock with adjustable spring preload/8.8 in
Front Tire	80/100-21

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. The product images shown are for illustration purposes only. Equipment illustrated and specifications may vary. Notably the 2022 KLX®230R S includes a steel fuel tank compared to the plastic fuel tank shown. Visit [Kawasaki-usa.com](https://www.kawasaki-usa.com) for full product details.