KLX®230SM









120/70-17

POWFR

Engine 4-stroke single, SOHC, air-cooled

Displacement 233cc

Bore x Stroke 67.0 x 66.0mm

Compression

Ratio

9.4:1

Fuel System DFI® with 32mm Keihin throttle body

Ignition TCBI Electronic Advance

Transmission 6-speed, return shift with wet multi-disc

manual clutch

Final Drive Chain

caliper (and ABS) Rear Brakes Single 220mm petal disc with single-piston caliper (and ABS)

DETAILS

Rear Tire

Front Brakes

Frame Type High-tensile steel, box-section perimeter

Single 300mm petal disc with a dual-piston

Rake/Trail 27.5°/4.6 in

Overall Length 80.7 in.

Overall Width 32.9 in.

Overall Height 44.1 in.

Clearance

Ground

Seat Height 33.3 in.

Curb Weight NON ABS: 295.5 lb. / 297.7 lb. CA model,

ABS: 297.7 lb. / 299.9 lb. CA model *

Fuel Capacity 2.0 gal.

Wheelbase 54.1 in.

Color Choices Lime Green, Oriental Blue

9.1 in.

Warranty 12 Month Limited Warranty

PERFORMANCE

Front
Suspension /
Wheel Travel

Rear
Suspension /
Wheel Travel

Uni-Trak® linkage system and single shock with adjustable spring preload/8.6 in

Wheel Travel

Front Tire

110/70-17



