VULCAN® 1700 VAQUERO® ABS







POWER			
Engine	4-stroke, 52-degree V-twin, liquid-cooled		
Displacement	1,700cc/103.7 cu in		
Bore x Stroke	102.0 x 104.0mm		
Compression Ratio	9.5:1		
Maximum Torque	107.6 lb-ft @ 2,750 rpm		

Torque	<u>G</u> - <i>p</i> -
Fuel System	DFI® with 42mm throttle bodies (2)
Ignition	TCBI with Electronic Advance
Transmission	6-speed with overdrive and positive neutral finder
Final Drive	Carbon fiber-reinforced belt
Electronic Rider Aids	Electronic Cruise Control, Kawasaki Advanced Coactive-Braking Technology (K-ACT) ABS

	rillat Drive	Carbon fiber-refillorced bett
	Electronic Rider Aids	Electronic Cruise Control, Kawasaki Advanced Coactive-Braking Technology (K-ACT) ABS
PERFORMANCE		
	Front Suspension / Wheel Travel	45mm Showa telescopic fork/5.5 in
	Rear Suspension / Wheel Travel	Swingarm with twin air-assisted shocks, with 4-way rebound damping/3.1 in
	Front Tire	130/90-16

Rear Tire	170/70-16
Front Brakes	Dual 300mm discs, dual four-piston calipers, K-ACT ABS
Rear Brakes	Single 300mm disc, twin-piston caliper, K-ACT ABS

n	ГΛ	П	2.
Ш	ΙΑ	Ш	-9

Frame Type	Steel, double-cradle with box-section single-tube backbone
Rake/Trail	30°/7.0 in
Overall Length	98.8 in
Overall Width	38.2 in
Overall Height	50.8 in
Ground Clearance	5.7 in
Seat Height	28.7 in
Curb Weight	844.5 lb*
Fuel Capacity	5.3 gal
Wheelbase	65.6 in
Special Features	Integrated audio system with SiriusXM Radio compatibility
Color Choices	Metallic Matte Twilight Blue
Warranty	36 Month Limited Warranty



