KLX[®]230R









POWER

Engine 4-stroke single, SOHC, air-cooled

Displacement 233cc

Bore x Stroke 67.0 x 66.0mm

Compression 9.4:1

Ratio

DFI® with 32mm Keihin throttle body **Fuel System**

Ignition TCBI Electronic Advance

Transmission 6-speed, return shift with wet multi-disc

manual clutch

Final Drive Chain **Rear Tire** 100/100-18

Front Brakes Single 240mm petal disc with a dual-

piston caliper

Rear Brakes Single 220mm petal disc with single-

piston caliper

PERFORMANCE

37mm telescopic fork/9.8 in **Front** Suspension / **Wheel Travel** Uni-Trak® linkage system and single shock Rear with adjustable spring preload/9.9 in Suspension / **Wheel Travel**

DETAILS

High-tensile steel, box-section perimeter **Frame Type**

Rake/Trail 26.5° / 4.4 in

Overall Length 80.5 in

Overall Width 33.1 in

Overall Height 47.2 in

Clearance

Ground

Seat Height 36.4 in

Curb Weight 253.6 lb* / 262.3 lb* CA Model

11.8 in

Fuel Capacity 1.7 gal

Wheelbase 53.5 in

Color Choices Lime Green, Battle Gray

Warranty 6 Months



Front Tire



80/100-21