MULE PRO-DXT™ FE DIESEL EPS







POWER

Engine 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel

Displacement 993cc

Maximum Torque 38.3 lb-ft @ 2,400 rpm

Bore x Stroke 2.91 x 3.03 in

Compression Ratio 23.5:1

Bosch in-line injection pump **Fuel System**

Continuously Variable Transmission (CVT) with (H,L,N,R) **Transmission**

Final Drive Selectable 2WD/4WD, shaft Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output

(max)

CAPABILITY

Rear Suspension /

Wheel Travel

Wheel Travel

Front Tires

Rear Tires 26 x 11.00-12

Steering Electric Power Steering (EPS), Tilt steering

Park Brake Type Independent, Mechanical Disc

Rear Brakes

Fuel Capacity 7.9 gal

Ground Clearance

Turning Radius 16.0 ft

Cargo Bed 42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-

Dimensions (LxWxH) person)

Cargo Bed Load 999 lb (3-person) / 350 lb (6-person)

10.2 in

Capacity

Payload Capacity 1,574 lb

Seating Capacity 3-person (1 row), 6 person (2 row)

Towing Capacity 2.000 lb

Lighting (2) Halogen headlights.

55 amp

Double wishbone/8.7 in Front Suspension /

Double wishbone/8.5 in (L) /8.7 in (R)

26 x 9 00-12

Dual Disc, 2 piston caliper

Dual Disc, 1 piston caliper

DETAILS

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 79.5 in

Curb Weight 1,971.3 lb*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters,

2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking

indicators, seatbelt reminder lamps

Wheel Type

Additional Features Roof, Horn, Universal Key, High Visibility Orange Seatbelts

Color Choices Bright White

Kawasaki STRONG 3-Year Limited Warranty Warranty



