MULE SX™ 4x4









POWER

Engine 4-stroke, single-cylinder, OHV, air-cooled

Displacement 401cc

Maximum Torque 21.4 lb-ft @ 2,400 rpm

Bore x Stroke 3.23 x 2.99 in

Compression Ratio 8.6:1

Fuel System Fuel Injection

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking No

Alternator Output 22.9 amp

(max)

Ground Clearance 6.7 in **Fuel Capacity** 4.2 gal

Turning Radius 10.8 ft

Cargo Bed

Dimensions (LxWxH)

399 lb

Cargo Bed Load Capacity

Payload Capacity

915 lb

Seating Capacity

1,100 lb** **Towing Capacity**

Lighting (2) Halogen headlights, tail/brake lights

35.6 x 40.9 x 9.6 in

CAPABILITY

MacPherson Strut/3.1 in Front Suspension / **Wheel Travel**

Rear Suspension / Wheel Travel

Unit Swingarm/3.1 in

Front Tires 24x9.00-10 **Rear Tires** 24x11.00-10

Rack-and-pinion Steering

Park Brake Type Independent, Mechanical Drum

Front Brakes Drum **Rear Brakes** Drum

DETAILS

Overall Length 106.7 in

Overall Width 52.6 in

Overall Height 70.9 in

Curb Weight 1,031.9 lb*

Wheelbase 70.1 in

Instruments Fuel gauge, hour meter, oil temp light, parking brake

light

Wheel Type Steel

Dark Royal Red, Timberline Green **Color Choices**

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

