## **MULE PRO-FX™ 1000 HD EDITION**







## **POWER**

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled, gas

Displacement 999cc

Maximum Torque 61.5 lb-ft @ 4,500 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 10.1:1

Fuel System DFI® with 38mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential with

differential lock

Engine Braking Yes

Alternator Output 90 amp

(max)

Ground Clearance 11.9 in (max), 11.8 in (std)

Fuel Capacity 7.9 gal

Turning Radius 16.0 ft

Cargo Bed Dimensions (LxWxH)

Cargo Bed Load

Capacity

Load 999/600 lb CA Model

2,000 lb

Payload Capacity 1,616.3/1,263.5 lb CA Model

Seating Capacity

**Towing Capacity** 

Lighting (2) Halogen headlights, (2) LED headlights

54.1 x 53.3 x 11.0 in

## **CAPABILITY**

Front Suspension / Double wishbone/11.0 in Wheel Travel

Rear Suspension /

Double wishbone/10.1 in

Independent, mechanical disc

Wheel Travel
Front Tires

Park Brake Type

26 x 9-12, radial

Rear Tires 26 x 11-12, radial

Wheel Type Steel

Steering Rack-and-pinion

Front Brakes Dual disc, 2-piston caliper

Rear Brakes Dual disc, 1-piston caliper

## **DETAILS**

Overall Length 136.6 in
Overall Width 64.0 in
Overall Height 81.1 in

**Dry Weight** 1,816.9/1,819.1 lb\*\* CA Model

Curb Weight 1,891.9/1,894.1 lb\* CA Model

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer, fuel gauge,

odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt

reminder lamps

Additional Features Roof, Rear Bumper, Additional Under Seat Storage Bin,

Rearview Mirror, Hydraulic Cargo Bed Lift, Self-Leveling Rear

Suspension, Anti-cinch Seatbelts

Color Choices Firecracker Red

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

All MULET® PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki-la.com for full product details.