

NEW 2026

Z900RS CAFE ABS



POWER

| | |
|-----------------------|--|
| Engine | 4-stroke, 4-cylinder, DOHC, 16-valve, liquid-cooled |
| Displacement | 948cc |
| Bore x Stroke | 73.4 x 56.0mm |
| Compression Ratio | 11.8:1 |
| Maximum Horsepower | 115.0 hp ¹ @ 9,300 rpm |
| Maximum Torque | 73.0 lb-ft @ 7,700 rpm |
| Fuel System | DFI® with 36mm throttle bodies |
| Ignition | TCBI with Electronic Advance |
| Transmission | 6-speed, return shift |
| Final Drive | Sealed chain |
| Electronic Rider Aids | Economical Riding Indicator, Electronic Cruise Control, Kawasaki Traction Control (KTRC), Anti-lock Brake System (ABS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Quick Shifter (KQS), IMU-Enhanced Chassis Orientation Awareness |

PERFORMANCE

| | |
|---------------------------------|---|
| Front Suspension / Wheel Travel | 41mm inverted telescopic fork with (12-way) adjustable compression and rebound (10-way) damping, spring preload (15-turn)/4.7 |
| Rear Suspension / Wheel Travel | Horizontal back-link swingarm with stepless adjustable rebound damping and spring preload/5.5 in |

| | |
|--------------|--|
| Front Tire | 120/70-17 |
| Rear Tire | 180/55-17 |
| Front Brakes | Dual 300mm discs with four-piston calipers and ABS |
| Rear Brakes | Single 250mm disc with single-piston caliper and ABS |

DETAILS

| | |
|----------------------|--|
| Frame Type | Trellis, high tensile steel |
| Rake/Trail | 25.0° / 3.9 in |
| Overall Length | 82.7 in |
| Overall Width | 33.3 in |
| Overall Height | 46.9 in |
| Ground Clearance | 5.3 in |
| Seat Height | 32.3 in |
| Estimated Dry Weight | 438.8 lb** |
| Curb Weight | 480.7 lb* |
| Fuel Capacity | 4.5 gal |
| Wheelbase | 57.7 in |
| Special Features | All-LED lighting, ERGO-FIT®, Smartphone Connectivity with available Voice Command and Turn-by-Turn Navigation via RIDELOGY THE APP MOTORCYCLE*** |
| Color Choices | Ebony |
| Warranty | 12 Month Limited Warranty |

Scan with camera to view videos, key features and more.



^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
^{**}Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
^{***}RIDELOGY THE APP and all trademarks, registered trademarks, logos, and copyrights are the property of their respective owners. Voice command and navigation functions will be available only to users who have purchased a license for those functions. Feature availability may vary to meet individual markets.
¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit [Kawasaki-la.com](https://www.kawasaki-usa.com) for full product details.