## **BRUTE FORCE® 450 4x4**









## **POWER**

Engine 4-stroke, single-cylinder, SOHC, liquid-cooled

Displacement 443c

Bore x Stroke 89.0 x 71.2mm

Compression Ratio 9.1:1

Maximum 32.0 hp<sup>1</sup> @ 7,000 rpm

Horsepower

Maximum Torque 24.3 lb-ft @ 6,500 rpm

Fuel System FI with 38mm throttle body

**Ignition** Digital DC-CDI

Transmission Automatic Continuously Variable Transmission (CVT) with

centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with dual-mode differential, shaft

## **DETAILS**

**Fuel Capacity** 

**Turning Radius** 

**Towing Capacity** 

**Total Rack Capacity** 

Rack Capacity, Front/

Steering

Rear

Lighting

Frame Type Double-cradle, high-tensile tubular steel

4.2 gal

1.050 lb

75/150 lb

taillight

225 lb

Conventional tie-rod

Tread Width 35.8/34.2 in

Overall Length 80.1 in

Overall Width 43.7 in

Overall Height 46.7 in

Seat Height 34.6 in

**Curb Weight** 683.4 lb\* / 685.6 lb\* CA Model

Wheelbase 47.8 i

Instruments Speedometer, tachometer, gear position indicator, fuel

gauge, clock, odometer, hour meter, trip meter, Differential

LED headlights, LED handlebar mounted light, Halogen

Lock/4WD indicator, etc.

Special Features KQR™ system-compatible front and rear cargo racks

Color Choices Grayish Blue, Firecracker Red

Warranty 12 Month Limited Warranty

## **CAPABILITY**

Front Suspension / Wheel Travel Dual A-arm, adjustable spring preload/7.6 in

Rear Suspension / Wheel Travel

Dual A-arm, adjustable spring preload/7.9 in

Specifications subject to change. Visit Kawasaki-la.com for full product details.

Front Tires

AT 24 x 8-12 AT 24 x 10-12

Rear Tires

Front Brakes
Rear Brakes

Dual 202mm discs Single 202mm disc

Ground Clearance

9.3 in

**Starting System** 

Electric

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are intended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to www.atvsafety.org. ©2025 Kawasaki Motors Corp., U.S.A.