2026 **BRUTE FORCE® 750 EPS**







10.5 ft

1,250 lb

264.5 lb

88.0/176.0 lb

All-LED lighting

37.0/35.6 in

86.0 in

46.1 in

47.6 in

Rack-and-pinion w/ Electric Power Steering (EPS)

Double-cradle, high-tensile tubular steel

PO	WER

Engine	4-stroke, V-twin, SOHC, liquid-cooled
Displacement	749cc
Bore x Stroke	85.0 x 66.0mm
Compression Ratio	9.3:1
Maximum Horsepower	50.0 hp1 @ 6,750 rpm
Maximum Torque	42.8 lb-ft @ 4,750 rpm
Fuel System	DFI® with two 34mm throttle bodies
Ignition	Digital DC-CDI
Transmission	Automatic Continuously Variable Transmission (CVT) with (H,L,N,R)
Final Drive	Selectable 2WD/4WD with variable control front differential lock, shaft

GAPADILITT		Seat Height	35.2 in
Front Suspension / Wheel Travel	Double wishbone, adjustable spring preload/6.9 in	Estimated Dry Weight	685.8 lb**
		Curb Weight	732.1 lb*
Rear Suspension / Wheel Travel	Double wishbone, adjustable spring preload/7.4 in	Wheelbase	50.6 in
Front Tires	AT 25 x 8-12	Instruments	Digital speedometer, 2WD/4WD drive indicator, fuel gauge, odometer, dual trip meters, dual hour meter, clock (12h/24h),
Rear Tires	AT 25 x 10-12		battery voltage, Kawasaki service reminder, oil change reminder, high beam, neutral, reverse, and warning lights
Front Brakes	Dual hydraulic 176mm discs with 2-piston calipers		(engine, coolant temperature, CVT, oil, EPS, and battery voltage)
Rear Brakes	Sealed, oil-bathed, multi-disc with independent park brake	Special Features	Full-color TFT Instrumentation w/ Smartphone Connectivity via RIDEOLOGY THE APP POWERSPORTS, KQR™ system
Ground Clearance	9.0 in/9.7 in (max preload)	Color Choices	Gravish Blue
Starting System	Electric		12 Month Limited Warranty
Fuel Capacity	5.0 gal	Warranty	12 Month Linned Warranty

Steering

Rear Lighting

Turning Radius

Towing Capacity

DETAILS

Frame Type

Tread Width

Overall Length

Overall Width

Overall Height

Total Rack Capacity

Rack Capacity, Front/





**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). 1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are recommended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to www.atvsafety.org. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki-la.com for full product details.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).