NEW 2026

BRUTE FORCE® 750 SE EPS









POWER

Engine 4-stroke, V-twin, SOHC, liquid-cooled

Displacement 749cc

Bore x Stroke 85.0 x 66.0mm

Compression Ratio

Maximum Torque 42.8 lb-ft @ 4,750 rpm

Fuel System DFI® with two 34mm throttle bodies

Digital DC-CDI Ignition

Transmission Automatic Continuously Variable Transmission (CVT) with

Final Drive Selectable 2WD/4WD with variable control front differential

lock, shaft

DETAILS

Tread Width

Curb Weight

Rear

Lighting

Turning Radius

Towing Capacity

Total Rack Capacity

Rack Capacity, Front/

Frame Type Double-cradle, high-tensile tubular steel 37.0/35.6 in

10.5 ft

1,250 lb

264.5 lb

88.0/176.0 lb

All-LED lighting

Overall Length 88.4 in **Overall Width** 46.7 in **Overall Height** 47.8 in **Seat Height** 35.2 in 723.2 lb** **Dry Weight**

Wheelbase 50.6 in

Instruments Digital speedometer, 2WD/4WD drive indicator, fuel gauge, odometer, dual trip meters, dual hour meter, clock (12h/24h),

battery voltage, Kawasaki service reminder, oil change reminder, high beam, neutral, reverse, and warning lights (engine, coolant temperature, CVT, oil, EPS, and battery

voltage)

769.5 lb*

Special Features WARN® VRX 25-S Powersport Winch, Front brush guard, Hand guards, Full-color TFT Instrumentation w/ Smartphone

Connectivity via RIDEOLOGY THE APP POWERSPORTS, KQR™

system

Color Choices Metallic Gold Sparkle Deep Green

Warranty 12 Month Limited Warranty

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone, adjustable spring preload/6.9 in

Rear Suspension /

Double wishbone, adjustable spring preload/7.4 in

Wheel Travel Front Tires

AT 25 x 8-12

AT 25 x 10-12

Front Brakes

Dual hydraulic 176mm discs with 2-piston calipers

Rear Brakes

Sealed, oil-bathed, multi-disc with independent park brake

Ground Clearance

8.7 in/9.6 in (max preload)

Starting System

Electric 5.0 gal

Fuel Capacity Steering

Rack-and-pinion w/ Electric Power Steering (EPS)

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are recommended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to www.atvsafety.org. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki-la.com for full product details.