ELIMINATOR® SE ABS









| D | N | ١ | M | Г | D |
|---|---|---|---|---|---|
| Г | u | ľ | N | E | π |

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled

Displacement 451cc

Bore x Stroke

70.0 x 58.6mm

Compression

11.3:1

Maximum Horsepower

Ratio

51 hp¹ @ 10,000 rpm

31.7 lb-ft @ 7,500 rpm

Maximum Torque

DFI® with 32mm throttle bodies

Fuel System
Ignition

TCBI w/ Digital Advance

Transmission

6-speed, return shift

Final Drive

Sealed chain

Electronic Rider

Aids

Anti-lock Brake System

PERFORMANCE

Front Suspension
/ Wheel Travel

41mm telescopic fork/4.7 in

Rear Suspension / Wheel Travel

Twin shocks/3.1 in

Front Tire

130/70-18

Rear Tire

150/80-16

Front Brakes Single 310mm disc with twin-piston caliper, and

ABS

Rear Brakes Single 220mm disc with single-piston caliper,

and ABS

DETAILS

Frame Type Trellis, high-tensile steel

Rake/Trail 30.0°/4.8 in

Overall Length 88.6 in

Overall Width 30.9 in

Overall Height 43.3 in

Ground

Clearance

5.9 in

Seat Height 28.9 in

Estimated Dry

Weight

363.8 lb**

Curb Weight 390.3 lb*

Fuel Capacity 3.4 gal

Wheelbase 59.8 in

Special Features

ERGO-FIT®, Smartphone Connectivity via

RIDEOLOGY THE APP

Color Choices Metallic

Metallic Imperial Red/Ebony

Warranty

12 Month Limited Warranty





*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki-la.com for full product details.