## **NEW 2026**

## KLE®500 SE ABS









	M	1	LA	П		D
Г	Ί	J	۲	П	CI	Λ

**Engine** 4-stroke, Parallel Twin, DOHC, liquid-cooled

Displacement 451cc

70.0 x 58.6mm

Bore x Stroke
Compression

Ratio

11.3:1

Maximum Horsepower 51 hp<sup>1</sup> @ 10,000 rpm

**Maximum Torque** 

31.7 lb-ft @ 7,500 rpm

**Fuel System** 

DFI® with 32mm throttle bodies

Ignition

TCBI with Electronic Advance

**Transmission** 

6-speed, return shift

Final Drive

' '

Sealed chain

Electronic Rider

Economical Riding Indicator, Selectable On/Off

Anti-lock Brake System (ABS)

## **PERFORMANCE**

Front Suspension / Wheel Travel 43mm inverted telescopic fork/8.3 in

Rear Suspension / Bottom-link Uni-Trak with adjustable spring preload/7.7 in

**Front Tire** 

90/90-21

**Rear Tire** 

140/70-17

Front Brakes

Single 300mm disc with 2-piston caliper and ABS

**Rear Brakes** 

Single 230mm disc with 2-piston caliper and ABS

## **DETAILS**

Frame Type Trellis, high tensile steel

Rake/Trail 28.0°/4.1 in

Overall Length 90.6 in

Overall Width 38.6 in

Overall Height 59.4 in (windscreen Hi) / 57.5 in (windscreen Lo)

**Ground Clearance** 7.3 in

Seat Height 34.3 in

**Estimated Dry** 

Weight

385.9 lb\*\* / 388.1 lb\*\* 50-State Model

**Curb Weight** 427.8 lb\* / 430.0 lb\* 50-State Model

Fuel Capacity 4.2 gal

Wheelbase 61.2 in

**Special Features** 

4.3-in All-digital TFT color Instrumentation, All-LED

lighting, Tall adjustable windscreen, Handguards, Larger aluminum skid plate, ERGO-FIT®,

Smartphone Connectivity via RIDEOLOGY THE APP MOTORCYCLE, USB Type-C outlet available as an

accessory

Color Choices

Pearl Blizzard White, Metallic Bluish Green

Warranty

12 Month Limited Warranty

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki-la.com for full product details.