KLX®140R L









POWER

Engine 4-stroke, single-cylinder, SOHC, air-cooled

Displacement 144cc

Bore x Stroke 58.0 x 54.4mm

Compression

Ratio

Front

9.5:1

Fuel System Keihin PB20 carburetor

Ignition Digital DC-CDI

Transmission 5-speed, return shift, with wet multi-disc

manual clutch

Final Drive Chain

Front Brakes

Single 220mm petal disc with a dual-piston

caliper

Rear Brakes Single 186mm petal disc with single-piston

caliper

PERFORMANCE

Suspension /
Wheel Travel

Rear
Suspension /
Wheel Travel

Uni-Trak® linkage system and single shock with piggyback reservoir, fully adjustable preload and 22-way rebound damping/7.1 in

Front Tire

70/100-19

33mm telescopic fork/7.1 in

DETAILS

Frame Type High-tensile steel, box-section perimeter

Rake/Trail 27.0°/3.8 in

Overall Length 74.6 in

Overall Width 31.1 in

Overall Height 42.3 in

Ground 10.0 in Clearance

Seat Height 31.5 in

Estimated Dry 196.2 lb**

Weight

Curb Weight 209.4 lb*

Fuel Capacity 1.5 gal

Wheelbase 50.6 in

Color Choices Lime Green, Bright White

Warranty 6 Month Limited Warranty



Rear Tire



90/100-16