ALL-NEW 2026

KLX[®]230 DF ABS







D	N	V	V	С	D
Г	U	٧	v	C	π

Engine 4-stroke single, SOHC, air-cooled

Displacement 233cc

Bore x Stroke 67.0 x 66.0mm

Compression

Ratio

Maximum 17.0 hp¹ @ 8,000 rpm

9.4:1

Horsepower

Maximum Torque

13.3 lb-ft @ 6,400 rpm

Fuel System

DFI® with 32mm throttle body

Ignition

TCBI with Electronic Advance

Transmission

6-speed

Final Drive

Sealed chain

PERFORMANCE

Front Suspension / Wheel Travel	37mm telescopic fork/7.9 in
Rear Suspension / Wheel Travel	Uni-Trak® linkage system and single shock with adjustable spring preload/8.8 in
Front Tire	2.75 x 21
Rear Tire	4.10 x 18

Front Brakes
Single 265mm petal disc with a dual-piston caliper

Rear Brakes
Single 220mm petal disc with single-piston caliper

DETAILS

Frame Type High-tensile steel, perimeter

Rake/Trail 24.6°/3.8 in

Overall Length 81.9 in

Overall Width 36.2 in

Overall Height 45.3 in

Ground Clearance 9.4 in

Seat Height 33.3 in

Estimated Dry

Weight

284.4 lb**

Curb Weight 302.1 lb*

Fuel Capacity 2.0 gal

Wheelbase 53.7 in

Special Features

ERGO-FIT®, Aluminum skid plate, Engine guards, Hand guards, All-digital Instrumentation with

Smartphone Connectivity

Color Choices Medium Cloudy Gray

Scan with camera to view videos, key features and more.



Specifications subject to change. Visit Kawasaki-la.com for full product details.