#### **ALL-NEW 2026**

# KLX<sup>®</sup>230 SHERPA S ABS







#### **POWER**

**Engine** 4-stroke single, SOHC, air-cooled

**Displacement** 233cc

**Bore x Stroke** 67.0 x 66.0mm

Compression

**Ratio** 

9.4:1

Maximum Horsepower 17.0 hp1 @ 8,000 rpm

**Maximum Torque** 

13.3 lb-ft @ 6,400 rpm

**Fuel System** 

DFI® with 32mm throttle body

Ignition

TCBI with Electronic Advance

Transmission

6-speed

**Final Drive** 

Sealed chain

## **PERFORMANCE**

Front Suspension / Wheel Travel	37mm telescopic fork/6.2 in
Rear Suspension / Wheel Travel	Uni-Trak® linkage system and single shock with adjustable spring preload/6.6 in
Front Tire	2.75 x 21
Rear Tire	4.10 x 18

**Front Brakes** Single 265mm petal disc with a dual-piston caliper

**Rear Brakes** Single 220mm petal disc with single-piston

### **DETAILS**

**Frame Type** High-tensile steel, perimeter

24.4°/3.8 in Rake/Trail

**Overall Length** 81.1 in

**Overall Width** 36.2 in

**Overall Height** 44.3 in

Ground Clearance

32.5 in

8.5 in

**Estimated Dry** 

Weight

**Seat Height** 

282.2 lb\*\* / 284.3 lb\*\* 50-State Model

**Curb Weight** 297.7 lb\* / 299.9 lb\* 50-State Model

**Fuel Capacity** 2.0 gal

Wheelbase 53.3 in

ERGO-FIT®, Even lower seat height, Aluminum **Special Features** 

skid plate, Hand guards, All-digital

Instrumentation with Smartphone Connectivity

**Color Choices** Whitish Beige

Scan with camera to view videos, key features and more.



Specifications subject to change. Visit Kawasaki-la.com for full product details.