KLX[®]230R









POWER

4-stroke, single-cylinder, SOHC, air-cooled **Engine**

Displacement 233cc

Bore x Stroke 67.0 x 66.0mm

Compression

Ratio

9.4:1

DFI® with 32mm Keihin throttle body **Fuel System**

Ignition TCBI with electronic advance

Transmission 6-speed, return shift with wet multi-disc

manual clutch

Final Drive Chain **Front Brakes**

Single 240mm petal disc with a dual-piston

caliper

Rear Brakes

DETAILS

Single 220mm petal disc with single-piston

caliper

High-tensile steel, box-section perimeter **Frame Type**

Rake/Trail 25.4° / 4.2 in

80.5 in **Overall Length**

Overall Width 33.3 in

Overall Height 47.2 in

11.4 in Ground Clearance

Seat Height 35.6 in

Estimated Dry 247.0 lb** / 249.1 lb** 50-State Model

Weight

Curb Weight

262.4 lb* / 264.5 lb* 50-State Model

Fuel Capacity 2.0 gal

Wheelbase 54.1 in

Color Choices Lime Green, Bright White

Warranty 6 Month Limited Warranty

PERFORMANCE

Front Suspension / **Wheel Travel** 37mm telescopic fork/9.8 in

Rear Suspension /

Wheel Travel

Uni-Trak® linkage system and single shock with adjustable spring preload/9.8 in

Front Tire

80/100-21

Rear Tire

100/100-18

Scan with camera to view videos, key features and more.

