MULE PRO-FXT™ 820 EPS









POWER

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812c

Maximum Torque 48.0 lb-ft @ 3,500 rpm

Bore x Stroke 72.0 x 66.5mm

Compression Ratio 9.5:1

Fuel System DFI® with 34mm throttle body (3)

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Ye

Alternator Output 75 amp

(max)

Rear Brakes Dual disc, 1-piston caliper

Ground Clearance 10.2 in

Fuel Capacity 7.9 gal

Turning Radius 16.0 ft

Cargo Bed 42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-

person)

Cargo Bed Load

Dimensions (LxWxH)

Capacity

999 lb (3-person)/350 lb (6-person)/348 lb CA Model

Payload Capacity 1,616.3/1,263.5 lb CA Model

Seating Capacity 3-person (1 row), 6 person (2 row)

Towing Capacity 2,000 lb

Lighting (2) Halogen headlights

CAPABILITY

Front Suspension / Double with Wheel Travel

Double wishbone/8.7 in

Rear Suspension / Wheel Travel

Double wishbone/8.5 in (L)/8.7 in (R)

Front Tires 26

26 x 9-12, radial

26 x 11-12, radial

Rear Tires
Wheel Type

Charl

Steering

Rack-and-pinion w/ Electric Power Steering (EPS), Tilt

steering

Park Brake Type

Independent, mechanical disc

Front Brakes

Dual disc, 2-piston caliper

DETAILS

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 77.6 in

Estimated Dry Weight 1,861

1,861.0/1,863.2 lb** CA Model

Curb Weight 1,949.2/1,951.4 lb* CA Model

Wheelbase 92.3 in

Instruments

Multi-function display includes digital speedometer, fuel

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and

parking indicators, seatbelt reminder lamps

Color Choices Timberline Green, Dark Royal Red

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki-la.com for full product details.