MULE PRO-MX™ LE







POWER

Engine 4-stroke, single cylinder, SOHC, 4-valve, liquid-cooled

Displacement

42.7 lb-ft @ 5,000 rpm **Maximum Torque**

Bore x Stroke 102.0 x 85.0mm

Compression Ratio

Fuel System DFI® with 44mm throttle body

Transmission Continuously Variable Transmission (CVT) with centrifugal

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output 35.7 amp

(max)

Ground Clearance 10.6 in **Fuel Capacity** 9.5 gal

Turning Radius 14.0 ft

Cargo Bed **Dimensions (LxWxH)**

33.4 x 44.1 x 9.1 in

Cargo Bed Load

Capacity

699 lb / 600 lb CA Model

Payload Capacity 1,200 lb / 1,100 lb CA Model

Seating Capacity

Towing Capacity 1,500 lb

Lighting (2) Halogen headlights, (2) LED headlights

CAPABILITY

Front Suspension / Double wishbone/8.6 in Wheel Travel

Rear Suspension / Double wishbone/9.1 in

Wheel Travel

Front Tires 25 x 8-12, radial **Rear Tires** 25 x 10-12, radial

Electric Power Steering (EPS), Tilt steering Steering

Park Brake Type Independent, mechanical disc **Front Brakes** Dual disc, 2-piston caliper **Rear Brakes**

Dual disc, 1-piston caliper

DETAILS

Overall Length 110.0 in **Overall Width** 60.0 in **Overall Height** 75.8 in

Dry Weight 1,519.2 lb** / 1,521.4 lb** CA Model **Curb Weight** 1,594.2 lb* / 1,596.4 lb* CA Model

Wheelbase 78.9 in

Instruments Multi-function display includes digital speedometer, fuel

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder

Additional Features Roof, Cast Aluminum Wheels

Color Choices Deep Blue

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



'Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki-la.com for full product details.