MULE PRO-MX™ SE







POWER

Engine 4-stroke, single cylinder, SOHC, 4-valve, liquid-cooled

Displacement 695cc

 Maximum Horsepower
 44.0 hp¹ @ 6,000 rpm

 Maximum Torque
 42.7 lb-ft @ 5,000 rpm

Bore x Stroke 102.0 x 85.0mm

Compression Ratio 10.3:1

Fuel System DFI® with 44mm throttle body

Transmission Continuously Variable Transmission (CVT) with centrifugal

clutch, (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential with

differential lock

Engine Braking Yes

Alternator Output 35.7 amp

(max)

Seating Capacity

Ground Clearance

Fuel Capacity

Turning Radius

Cargo Bed Load

Payload Capacity

(LxWxH)

Capacity

Cargo Bed Dimensions

Towing Capacity 1,500 lb

Lighting (2) Halogen headlights, (2) LED headlights

10.6 in

9.5 gal

14.0 ft

33.4 x 44.1 x 9.1 in

699 lb / 600 lb CA Model

1,200 lb / 1,100 lb CA Model

DETAILS

Overall Length 111.4 in
Overall Width 60.0 in
Overall Height 75.8 in

Estimated Dry Weight 1,550.1 lb** / 1,552.3 lb** CA Model

Curb Weight 1,622.9 lb* / 1,625.1 lb* CA Model

Wheelbase 78.9 in

Instruments Multi-function display includes digital speedometer, fuel gauge,

odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential

indicator lamp, seatbelt reminder lamps

Additional Features Roof, WARN® VRX 35 Winch, Cast Aluminum Wheels, Painted

Body Panels

Color Choices Gold

Warranty Kawasaki STRONG 3-Year Limited Warranty

CAPABILITY

Front Suspension / Wheel Travel

t Suspension / Double wishbone/8.6 in

Rear Suspension /

/ Double wishbone/9.1 in

Wheel Travel

25 x 8-12, radial

Front Tires
Rear Tires

25 x 10-12, radial

Steering

Electric Power Steering (EPS), Tilt steering

Park Brake Type

Independent, mechanical disc

Front Brakes

Dual disc, 2-piston caliper

Rear Brakes

Dual disc, 1-piston caliper

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki-la.com for full product details.