2027

BRUTE FORCE® 300

Kawasaki
Let the Good Times Roll®

SMOKY GRAY

FIRECRACKER RED

POWER

Engine	4-stroke, single-cylinder, SOHC, liquid-cooled
Displacement	271cc
Bore x Stroke	72.7 x 65.2mm
Compression Ratio	10.6:1
Maximum Horsepower	21.0 hp[1] @ 7,500 rpm
Maximum Torque	16.2 lb-ft @ 6,500 rpm
Fuel System	FI with 32mm throttle body
Ignition	DC-CDI
Transmission	Automatic Continuously Variable Transmission (CVT) with centrifugal clutch (H,L,N,R)
Final Drive	2WD, shaft

CAPABILITY

Front Suspension / Wheel Travel	Double wishbone, adjustable spring preload/5.3 in
Rear Suspension / Wheel Travel	Swingarm with single shock, adjustable spring preload/5.5 in
Front Tires	Maxxis® AT 22 x 7-10
Rear Tires	Maxxis® AT 22 x 10-10
Front Brakes	Dual 180mm discs
Rear Brakes	Single 180mm disc
Ground Clearance	6.1 in
Starting System	Electric
Fuel Capacity	3.2 gal
Steering	Conventional tie-rod
Turning Radius	9.2 ft
Towing Capacity	500 lb
Total Rack Capacity	110 lb
Rack Capacity, Front/ Rear	44/66 lb
Lighting	LED headlights, LED handlebar mounted light, Halogen taillight

DETAILS

Frame Type	Double-cradle, tubular steel
Tread Width	33.5/32.7 in
Overall Length	75.4 in
Overall Width	42.5 in
Overall Height	46.1 in
Seat Height	33.3 in
Estimated Dry Weight	527.0 lb** / 529.2 lb** CA Model
Curb Weight	551.3 lb* / 553.5 lb* CA Model
Wheelbase	45.9 in
Instruments	Speedometer, tachometer, gear position indicator, fuel gauge, clock, odometer, hour meter, trip meter, etc.
Color Choices	Smoky Gray, Firecracker Red
Warranty	12 Month Limited Warranty

Scan with camera to view videos, key features and more.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
[1]This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are intended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to www.atvsafety.org. ©2026 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit Kawasaki-la.com for full product details.