

NUEVA 2026

TERYX® 4 H2



VERDE LIME




POTENCIA	
Motor	4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled
Cilindrada	999cc
Potencia máxima	250.0 hp¹ @ 9,000 rpm
Par máximo	146.3 lb-ft @ 8,800 rpm
Diámetro x Carrera	73.4 x 59.0mm
Relación de compresión	7.8:1
Sistema de combustible	DFI® with (4) 40mm throttle bodies with dual injection; Kawasaki Supercharger
Ignition	TCBI with electronic advance
Arranque	Electric
Transmisión	Automatic CVT with centrifugal clutch (H,L,N,R)
Transmisión final	Selectable 2WD/4WD with locking front differential, shaft
Freno motor	Yes

Dimensiones del compartimento de carga (LxAxA)	14.6 x 33.1 x 9.1 in
Capacidad de carga del compartimento de carga	300 lb
Capacidad de carga útil	1,076 lb
Capacidad de asientos	4-person (2 row), bucket seats with 4-point seatbelts
Luces	All-LED lighting

CAPACIDAD	
Suspensión delantera/ recorrido del neumático	Double wishbone, FOX 3.0 Internal Bypass shocks, adjustable compression damping and adjustable preload/23.2 in
Suspensión trasera/ recorrido del neumático	4-link trailing-arm rear suspension, FOX 3.0 Internal Bypass Shocks, adjustable compression damping and adjustable preload/24.0 in
Neumáticos delanteros	Maxxis® Carnivore Plus 33 x 10.00R16
Neumáticos traseros	Maxxis® Carnivore Plus 33 x 10.00R16
Dirección	Electric Power Steering (EPS) / rack-and-pinion
Freno delantero	270mm dual hydraulic discs with 3-piston calipers
Freno trasero	270mm dual hydraulic discs with 2-piston calipers
Altura libre al suelo	16.5 in (max) / 16.1 in (std)
Capacidad de combustible	14.8 gal
Radio de giro	24.9 ft

DETALLES	
Cuadro	Ladder type, tubular steel
Longitud total	159.4 in
Anchura total	74.0 in
Altura total	71.5 in
Peso seco estimado	2,291.0 lb** / 2,293.2 lb** CA Model
Peso en orden de marcha	2,425.5 lb* / 2,427.7 lb* CA Model
Distancia entre ejes	126.0 in
Instrumentación	Digital speedometer, tachometer, fuel gauge, gear indicator (L, H, N, R), Driving Mode (2WD/4WD/4WD+Diff Lock), Power Mode (Full/Mid/Low), Economical Riding Indicator, connected indicator, clock, odometer, dual trip meters, total time, trip time, average speed, engine temperature, intake air temperature, battery voltage, boost pressure, CTV temperature, seatbelt warning lamp, maintenance reminder, oil warning lamp, engine check lamp, engine temperature warning lamp, neutral indicator, reverse indicator, headlight high-beam indicator, parking indicator lamp, battery warning lamp, EPS warning lamp, and CVT belt warning lamp
Características adicionales	7-in Full-color TFT Instrumentation with Smartphone Connectivity via RIDELOGY THE APP POWERSPORTS, Steel skid-plates w/ drain holes, ERGO-FIT®, 2 DC outlets, 2 USB ports, 8 cup holders, Additional storage
Opciones de color	Lime Green



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visite [Kawasaki-la.com](https://www.kawasaki-la.com) para obtener detalles completos del producto.