

2027

NINJA® 500 ABS

Kawasaki
Let the Good Times Roll®



-  NEGRO METALLIC FLAT SPARK/NEGRO METALLIC SPARK
-  VERDE METALLIC YELLOWISH/NEGRO EBONY
-  GALAXY SILVER/METALLIC MATTE GRAPHENESTEEL GRAY



POTENCIA		Frenos delanteros	Single 310mm semi-floating disc with 2-piston caliper (and ABS)
Motor	4-stroke, Parallel Twin, DOHC, liquid-cooled	Frenos traseros	Single 220mm disc with single-piston caliper (and ABS)
Cilindrada	451cc	DETALLES	
Diámetro por carrera	70.0 x 58.6mm	Tipo de chasis	Trellis, high-tensile steel
Relación de compresión	11.3:1	Ángulo de dirección/Avance	24.5° / 3.6 in
Potencia máxima	51.0 hp ¹ @ 10,000 rpm	Largo total	78.5 in
Par motor máximo	31.7 lb-ft @ 7,500 rpm	Ancho total	28.7 in
Sistema de combustible	DFI® with dual 32mm throttle bodies	Altura del asiento	44.1 in
Encendido	TCBI with Digital Advance	Distancia al suelo	5.7 in
Transmisión	6-speed	Altura del asiento	30.9 in
Transmisión final	Sealed chain	Peso seco estimado	346.2 lb** (ABS), 341.8 lb** (non-ABS) 50-State Model; 344.0 lb** (ABS), 339.6 lb** (non-ABS) 49-State Model
Asistencia electrónica para el piloto	Economical Riding Indicator, Anti-lock Brake System (ABS only)	Peso en orden de marcha	377.1 lb* (ABS), 372.6 lb* (non-ABS) 50-State Model; 374.9 lb* (ABS), 370.4 lb* (non-ABS) 49-State Model
RENDIMIENTO		Depósito de combustible	3.7 gal
Suspensión delantera/recorrido del neumático	41mm hydraulic telescopic fork/4.7 in	Distancia entre ejes	54.1 in
Suspensión trasera/recorrido del neumático	Horizontal back-link with adjustable spring preload/5.1 in	Características especiales	ERGO-FIT®, LCD instrumentation with Smartphone Connectivity via RIDEOLGY THE APP MOTORCYCLE
Neumático delantero	110/70-17	Colores disponibles	Metallic Flat Spark Black/Metallic Spark Black, Metallic Yellowish Green/Ebony, Galaxy Silver/Metallic Matte Graphenesteel Gray
Neumático trasero	150/60-17	Garantía	12 Month Limited Warranty

Escanear con cámara para ver videos, características clave y más.



^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
^{**}Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
^{***}RIDEOLGY THE APP and all trademarks, registered trademarks, logos, and copyrights are the property of their respective owners. Voice command and navigation functions will be available only to users who have purchased a license for those functions. Feature availability may vary to meet individual markets.
¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visite [Kawasaki-la.com](https://www.kawasaki-la.com) para obtener detalles completos del producto.