

2027

VERSYS® 650 ABS

Kawasaki
Let the Good Times Roll®

 GRIS METALLIC CARBON/NEGRO METALLIC SPARK



POTENCIA

Motor	4-stroke, 2-cylinder, DOHC, 8 valves, liquid-cooled
Cilindrada	649cc
Diámetro por carrera	83.0 x 60.0mm
Relación de compresión	10.8:1
Potencia máxima	66.0 hp ¹ @ 8,500 rpm
Par motor máximo	45.0 lb-ft @ 7,000 rpm
Sistema de combustible	DFI® with 38mm Keihin throttle bodies (2)
Encendido	TCBI with Electronic Advance
Transmisión	6-speed with positive neutral finder
Transmisión final	Sealed chain
Asistencia electrónica para el piloto	Kawasaki TRaction Control (KTRC), Anti-lock Brake System (ABS), Economical Riding Indicator

RENDIMIENTO

Suspensión delantera/recorrido del neumático	41mm telescopic fork with stepless adjustable rebound and spring preload/5.9 in
Suspensión trasera/recorrido del neumático	Single offset laydown shock with remote adjustable spring preload/5.7 in
Neumático delantero	120/70 ZR-17
Neumático trasero	160/60 ZR-17

Frenos delanteros	Dual 300mm petal-style discs with 2-piston calipers and ABS
Frenos traseros	Single 250mm petal-style disc with single-piston caliper and ABS

DETALLES

Tipo de chasis	Double pipe diamond frame constructed from high-tensile steel
Ángulo de dirección/Avance	25° /4.3 in
Largo total	85.2 in
Ancho total	33.1 in
Altura del asiento	53.5 in/55.9 in (windscreen down/up)
Distancia al suelo	6.7 in
Altura del asiento	33.3 in
Peso seco estimado	444.1 lb** (+ approx. 20 lb** w/ saddlebags & hand guards)
Peso en orden de marcha	482.9 lb* (+ approx. 20 lb* w/ saddlebags & hand guards)
Depósito de combustible	5.5 gal
Distancia entre ejes	55.7 in
Características especiales	TFT color instrumentation with Smartphone Connectivity via RIDEOLGY THE APP MOTORCYCLE, Adjustable windscreen, Hand guards, Clean-mount hard saddlebag system featuring QQR™ mounts
Colores disponibles	Metallic Carbon Gray/Metallic Spark Black
Garantía	Garantía limitada de 12 meses

Escanear con cámara para ver videos, características clave y más.



^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
^{**}Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
^{***}RIDEOLGY THE APP and all trademarks, registered trademarks, logos, and copyrights are the property of their respective owners. Voice command and navigation functions will be available only to users who have purchased a license for those functions. Feature availability may vary to meet individual markets.
¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visite [Kawasaki-la.com](https://www.kawasaki-la.com) para obtener detalles completos del producto.